## Series 22, 23

- Features
- Snap fits into .312" panel hole
- Body and lens are one piece construction
- LED, incandescent, and neon illumination

## Specifications • Body & Lens Material:

- Wire Gauge:
- Wire Strip:
- Panel Thickness:
- Certifications:

18 ga. 1/2" .025" to .060" max Contact Us

Polycarbonate

-.95 Series 23 .50 ► 6.00 ◀.50 ► Series 22 1.55 6.00 1.55 .37 Series 22 (with tabs) `Ø .312" Mounting Hole

Series		Lamp		Termina	tion Ba	ase	Bez	el		Len	s
XX	11	XX	_	x		х <sup>′</sup>	' <u>x</u>		XXX		<u>X</u> 0
22 23	Voltage 2 6 14 28 125 6 14 28	Type LED LED LED LED LED INCAND INCAND INCAND	Code 10 11 12 13 15 <sup>3</sup> 32 35 39	<u>Style</u> 6" Wire .187 Tabs Special	Code Color 1 N/A 3 <sup>2</sup> X	Code 0	Finish None	Code 0	<u>Style</u> Semi-Dome Diamonds Cylinder Rings Dome Plain	<u>Code</u> 343 356 362	Color RedCode 1Amber2Clear3 1Green4Blue5
	125 250	NEON NEON	50 52								
	6 14 28 125	ViviBright LED ViviBright LED ViviBright LED ViviBright LED ViviBright LED ViviBright LED	60 61 62 63 65 <sup>3</sup> 66 <sup>3</sup>								.38
		Custom	XX					- - .0		40	.25

## Additional Options Available:

Contact sales@solico.com

1. Clear lens has white LED

2. Available with LED (2V) and incandescent lamps only

3. Wire leads only

4 Sorenson Lighted Controls, Inc. www.solico.com 1-800-275-7089 (860) 527-3092

Lens 34

Lens 35

Lens 36